

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2020/0196746 A1 Brensinger et al.

Jun. 25, 2020 (43) **Pub. Date:**

(54) T-LINK HINGE MECHANISM

(71) Applicant: NEMO EQUIPMENT, INC., Dover, NH (US)

(72) Inventors: Camon Brensinger, Stratham, NH (US); Patrick McCluskey, Lee, NH (US); Zackary Kamen, Newburyport,

MA (US)

(21) Appl. No.: 16/725,666

Dec. 23, 2019 (22) Filed:

Related U.S. Application Data

- (60) Division of application No. 16/545,743, filed on Aug. 20, 2019, Continuation of application No. 15/879, 007, filed on Jan. 24, 2018, now Pat. No. 10,390,609.
- (60) Provisional application No. 62/449,818, filed on Jan. 24, 2017.

Publication Classification

(51)	Int. Cl.	
	A47B 3/12	(2006.01)
	A47B 3/00	(2006.01)
	A47B 13/00	(2006.01)
	A47B 37/04	(2006.01)
	F16B 12/44	(2006.01)

A47B 3/06	(2006.01)
A47B 3/08	(2006.01)
A47B 13/08	(2006.01)
A47B 3/083	(2006.01)

(52) U.S. Cl.

CPC A47B 3/12 (2013.01); A47B 3/002 (2013.01); A47B 13/003 (2013.01); A47B 37/04 (2013.01); F16B 12/44 (2013.01); A47B 3/06 (2013.01); F16B 2012/446 (2013.01); A47B 13/088 (2013.01); A47B 3/083 (2013.01); A47B 2220/0072 (2013.01); A47B 2200/001 (2013.01); A47B 2003/0806 (2013.01); A47B 3/0803 (2013.01)

(57)ABSTRACT

A T-link hinge for hingeably connecting first and second members comprises a link portion having a T-shaped crosssection including a top region and a bottom region, wherein the top region has a width greater than a width of the bottom region. The link portion comprises first and second thru holes formed in the bottom region of the link portion adjacent each the respective first and second ends of the link portion. Each of the first and second members to which the link portion is to be mounted includes thru holes. In an assembled configuration of the link portion and the first and second members, the thru holes formed on the first and second members axially align with the pair of thru holes in the link portion and are connected by first and second pins.

